


IPP Scheme

- Help users distinguish IPP objects from “other” web objects.
- Users will always see `ipp://` as URL format for IPP Printers and IPP Print Jobs.
- `ipp://` URLs are always used inside the `application/ipp` MIME object.
- The HTTP layer uses `http://` URLs to transfer the `application/ipp` MIME objects.

IPP Scheme Usage



IPP Scheme - Security (Client)

– Translation from ipp:// to http:// (or https://).

– Syntax :

ipp://host [:port]/<ipp-specific-path>;parameters

– Parameters are currently for security only

- AUTH = secure-protocol
- Secure-protocol := “TLS” | “SSL3” | “DAA”
- Parameters translated into HTTP header.

IPP Scheme - Security(Server)

- Job URI generated in response to a client created job request.
- URIs will use IPP scheme with IPP security parameters.
- Specified security-protocol must match.
- Unless other port is specified, (e.g. 443 to use https://), IPP default port 631 is used.

IPP Scheme - Example 1

- Example using TLS.
- `ipp://www.xerox.com/printer-wiley;AUTH=TLS`
- TLS is used as secure transport protocol.
- Translate to HTTP scheme:
 - `http://www.xerox.com:631/printer-wiley`
- HTTP Header:
 - Upgrade: TLS/1.0
- This is the standard HTTP with TLS method.

IPP Scheme - Example 2

- Example using no security.
- `ipp://www.xerox.com/printer-wiley/`
 - Port 631 is used as default port.
- `ipp://www.xerox.com:80/printer-wiley`
 - Port 80 is used for connecting to the printer.
- `ipp://www.xerox.com:631/es-adstc/printer-wiley`
 - Port 631 is explicitly mentioned.

IPP Scheme - Example 3

- Example using DAA.
- `ipp://www.xerox.com:80/printer-wiley;AUTH=DAA`
- DAA is used as a security channel.
- Port 80 is used for communication.

IPP Scheme - Translation

Example

- *Translation into HTTP header.*
- POST /printer-wiley/es-adstc-queue HTTP/1.1
- Host: www.xerox.com:631
- Security-Protocol: TLS
- Content-type: application/ipp
- Transfer-Encoding: chunked

IPP Scheme - Server Example

- *At the server end.*
- `ipp://www.xerox.com/printer-wiley/job-status/`
 - Client can use this to query job status.
- `ipp://www.xerox.com/printer-wiley/es-adstc-submit;AUTH=TLS`
 - Client can use this for job submission.
 - Security protocol preserved.