

Working Draft, June 2, 2003
Maturity Level: Development

Text that has been drastically changed and needs review is highlighted like this

The Printer Working Group (PWG) Standard for Internet Printing Protocol (IPP): Page Overrides

Abstract: This IPP specification extends the IPP Model and Semantics [rfc2911] object model by relaxing the restriction that each attribute value is the same for all pages within a Document. For example, with this extension, page 1 of a job could have a different media than the other pages in the job.

This extension supports page Overrides by adding a new Template attribute: "overrides. Each 'collection' value contains attributes that identify the attributes to Override and their associated values as well as the range of pages for the Override. The range of pages is specified by the "document-copies" attribute and the "pages" attribute to allow Overrides of pages in specific copies of the document.



Working Draft, June 2, 2003
Maturity Level: Development

The Printer Working Group (PWG) Standard for Internet Printing Protocol (IPP): Page Overrides

This version of the PWG Proposed Standard is available electronically at:

ftp://www.pwg.org/pub/pwg/ipp/new_EXC/wd-ippOverride10-20030527.pdf, .doc

This document is a Working Draft for an IEEE-ISTO PWG Candidate Standard. For a definition of a "PWG Candidate Standard" and its transition to a "PWG Standard", see: <ftp://ftp.pwg.org/pub/pwg/general/pwg-process.pdf>. After approval by the PWG (by a Last Call) to transition a PWG Working Draft to a PWG Candidate Standard, the resulting PWG Candidate Standard will be available electronically at: <ftp://ftp.pwg.org/pub/pwg/cs/>. After approval by the PWG (by a Last Call) to transition a PWG Candidate Standard to a PWG Standard, the resulting PWG Standard will be available electronically at: <ftp://ftp.pwg.org/pub/pwg/standards/>.

Copyright (C) 2003, IEEE ISTO. All rights reserved.

This document may be copied and furnished to others, and derivative works that comment on, or otherwise explain it or assist in its implementation may be prepared, copied, published and distributed, in whole or in part, without restriction of any kind, provided that the above copyright notice, this paragraph and the title of the Document as referenced below are included on all such copies and derivative works. However, this document itself may not be modified in any way, such as by removing the copyright notice or references to the IEEE-ISTO and the Printer Working Group, a program of the IEEE-ISTO.

Title: The Printer Working Group Standard for the Internet Printing Protocol (IPP): Page Overrides

The IEEE-ISTO and the Printer Working Group DISCLAIM ANY AND ALL WARRANTIES, WHETHER EXPRESS OR IMPLIED INCLUDING (WITHOUT LIMITATION) ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

The Printer Working Group, a program of the IEEE-ISTO, reserves the right to make changes to the document without further notice. The document may be updated, replaced or made obsolete by other documents at any time.

The IEEE-ISTO takes no position regarding the validity or scope of any intellectual property or other rights that might be claimed to pertain to the implementation or use of the technology described in this document or the extent to which any license under such rights might or might not be available; neither does it represent that it has made any effort to identify any such rights.

The IEEE-ISTO invites any interested party to bring to its attention any copyrights, patents, or patent applications, or other proprietary rights which may cover technology that may be required to implement the contents of this document. The IEEE-ISTO and its programs shall not be responsible for identifying patents for which a license may be required by a document and/or IEEE-ISTO Industry Group Standard or for conducting inquiries into the legal validity or scope of those patents that are brought to its attention. Inquiries may be submitted to the IEEE-ISTO by e-mail at:

ieee-isto@ieee.org.

The Printer Working Group acknowledges that the IEEE-ISTO (acting itself or through its designees) is, and shall at all times, be the sole entity that may authorize the use of certification marks, trademarks, or other special designations to indicate compliance with these materials.

Use of this document is wholly voluntary. The existence of this document does not imply that there are no other ways to produce, test, measure, purchase, market, or provide other goods and services related to its scope.

About the IEEE-ISTO

The IEEE-ISTO is a not-for-profit corporation offering industry groups an innovative and flexible operational forum and support services. The IEEE-ISTO provides a forum not only to develop standards, but also to facilitate activities that support the implementation and acceptance of standards in the marketplace. The organization is affiliated with the IEEE (<http://www.ieee.org/>) and the IEEE Standards Association (<http://standards.ieee.org/>).

For additional information regarding the IEEE-ISTO and its industry programs visit <http://www.ieee-isto.org>.

About the IEEE-ISTO PWG

The Printer Working Group (or PWG) is a Program of the IEEE Industry Standards and Technology Organization (ISTO) with member organizations including printer manufacturers, print server developers, operating system providers, network operating systems providers, network connectivity vendors, and print management application developers. The group is chartered to make printers and the applications and operating systems supporting them work together better. All references to the PWG in this document implicitly mean "The Printer Working Group, a Program of the IEEE ISTO." In order to meet this objective, the PWG will document the results of their work as open standards that define print related protocols, interfaces, procedures and conventions. Printer manufacturers and vendors of printer related software will benefit from the interoperability provided by voluntary conformance to these standards.

In general, a PWG standard is a specification that is stable, well understood, and is technically competent, has multiple, independent and interoperable implementations with substantial operational experience, and enjoys significant public support.

For additional information regarding the Printer Working Group visit: <http://www.pwg.org>

Contact information:

IPP Web Page: <http://www.pwg.org/ipp/>

IPP Mailing List: ipp@pwg.org

To subscribe to the ipp mailing list, send the following email:

- 1) send it to majordomo@pwg.org
- 2) leave the subject line blank
- 3) put the following two lines in the message body:
subscribe ipp
end

Implementers of this specification are encouraged to join the IPP Mailing List in order to participate in any discussions of clarifications or review of registration proposals for additional names. Requests for additional extensions, for inclusion in this specification, should be sent to the IPP Mailing list for consideration. In order to reduce spam the mailing list rejects mail from non-subscribers, so you must subscribe to the mailing list in order to send a question or comment to the mailing list.

Table of Contents

1	Introduction.....	6
2	Terminology.....	6
2.1	Conformance Terminology.....	7
2.2	Other Terminology.....	7
2.2.1	Impression.....	7
2.2.2	Job Creation operation.....	7
2.2.3	Overrides.....	7
2.2.4	Page.....	7
2.2.5	Sheet.....	7
3	Overview 8	
3.1	Numbering of Components.....	8
4	New Job Template Attributes.....	8
4.1	overrides (1setOf collection).....	9
4.1.1	Pages (1setOf rangeOfInteger(1:MAX)).....	10
4.1.2	document-numbers (1setOf rangeOfInteger (1:MAX)).....	10
4.1.3	document-copies (1setOf rangeOfInteger (1:MAX)).....	10
4.1.4	Overriding template attributes.....	11
4.1.5	Handling of Error conditions.....	14
4.1.6	Rationale for not having a “overrides-default” attribute.....	14
4.1.7	overrides-supported (1setOf type2 keyword).....	14
5	Examples 15	
5.1	First Page of Single Document is Letterhead.....	15
5.1.1	Request.....	15
5.2	First Page of Several Documents is Blue.....	15
5.2.1	Request.....	15
6	Conformance Requirements.....	16
7	IANA Considerations.....	17
7.1	Attribute Registration.....	17
7.2	Keyword Attribute Value Registrations.....	17
8	Internationalization Considerations.....	17
9	Security Considerations.....	18
10	References.....	18
11	Author's Addresses.....	18
12	Change Log (informative).....	20
13	Appendix 1 Changes from IEEE ISTO 5100.4-2001.....	20

Table of Tables

Table 1 "overrides" member attributes	9
Table 2 Job Template Attribute Override Scope	12

1 Introduction

The Internet Printing Protocol (IPP) is an application level protocol for distributed printing using Internet tools and technologies. IPP version 1.1 (IPP/1.1) requires that each attribute value be the same for all pages within a document within a job. This document defines OPTIONAL extensions to the IPP/1.1 model which relax this restriction and allow pages to have attributes that are Overrides. For example, with this extension, page 1 of a Document could have a different media or different value of "sides" from the other pages in the document. Another example is that the 1st copy of the Document could be printed single-sided on transparency and the remaining copies printed 4-up two-sided and stapled. Page Overrides always apply to pages within a document without regard to the "multiple-documents-handling" attribute.

This extension supports page Overrides by adding a new Template attribute: "overrides" (1setOf collection). Each 'collection' value for "overrides" contains

- A MANDATORY member attribute that identifies the overridden pages, namely "pages".
- A OPTIONAL member attribute that identifies the documents containing the overridden pages, namely "document-numbers". This attribute MUST be supplied if the Override is specified as a Job Template attribute and the Overrides apply only to specific Documents. If this member attribute is not supplied, the Override applies to all Documents in the Job.
- An OPTIONAL member attribute that identifies the document copies of the specified documents, i.e. "document-copies". If this member attribute is absent, the Overrides apply to all document copies.
- The 'collection' value also contains one or more attributes that are Overrides for the identified pages, e.g. "sides" or "media".

This document is a proposal for an extension to IPP/1.0 and IPP/1.1. This document replaces the obsolete "Override Attributes for Documents and Pages document" [PWG5100.4-2001]. This specification provides Overrides at the page level. The "overrides" Job Template attribute defined in this specification replaces the deprecated ""page-overrides" Job Template attribute. Other specifications outside the scope of this document provide the remaining features from the obsolete specification such as "document-overrides", "pages-per-subset", and "job-warnings-count". See Appendix 1 Changes from IEEE ISTO 5100.4-2001 for details.

2 Terminology

This section defines the following additional terms that are used throughout this document:

2.1 Conformance Terminology

Capitalized terms, such as **MUST**, **MUST NOT**, **REQUIRED**, **SHOULD**, **SHOULD NOT**, **MAY**, and **OPTIONAL**, have special meaning relating to conformance as defined in RFC 2119 [rfc2119]. If an implementation supports the extension defined in this document, then these terms apply; otherwise, they do not. These terms define conformance to *this document (and [rfc2911]) only*; they do not affect conformance to other documents, unless explicitly stated otherwise. For example, the term **REQUIRED** in this document means “**REQUIRED** if this **OPTIONAL** Override specification is implemented”.

The term **CONDITIONALLY REQUIRED** means that the Printer **MUST** support the feature, if the specified condition is true. The term **CMUST** means **MUST** if the specified “condition” is true.

2.2 Other Terminology

This document uses the same terminology as [rfc2911], such as “**client**”, “**Printer**”¹, “**attribute**”, “**attribute value**”, “**keyword**”, “**Job Template attribute**”, “**Operation attribute**”, “**operation**”, “**request**”, “**response**”, and “**support**” with the same meaning. In addition, the following terms are defined for use in this document:

2.2.1 Impression

An “impression” is the image (possibly many PDL pages in different configurations) imposed onto a single side of a media sheet.

2.2.2 Job Creation operation

Operations that create Job objects, specifically: Print-Job, Print-URI, and Create-Job as defined in [rfc2911].

2.2.3 Overrides

In IPP/1.1, each attribute value is the same for the entire Job. When an attribute is an “Overrides” attribute, it is different for identified pages. Pages can be identified within a Document or a specific copy of a Document.

2.2.4 Page

The term “Page” used throughout this document as a synonym for PDL page. A “PDL Page” is a page according to the definition of pages in the language used to express the document data. Note: if the PDL contains multiple original source pages that have been placed on a single page, then the PDL page count is 1. Rfc2911 uses the term print stream page for PDL Page.

2.2.5 Sheet

A Sheet is the unit of media that a printer puts marks on. It is the most basic unit of output from a printer. A printer may mark on one side or on both sides of a sheet.

¹ [rfc2911] uses the terms “Printer object” and “Printer” interchangeably to mean the same thing. For simplicity, this document uses the term “Printer” exclusively, except for definitions copied directly from [rfc2911]. None the less, the intent is as in [rfc2911]: a Printer is an object that MAY be hosted in the device or in a server as in [rfc2911].

© 2001, 2003, IEEE Industry Standards and Technology Organization. All rights reserved.

The IEEE-ISTO is affiliated with the IEEE and the IEEE Standards Association.

IEEE-ISTO 5100.n is a trademark of the IEEE-ISTO.

3 Overview

In IPP 1.1, all attributes that a client includes with Job Creation operations affect the entire Job in a uniform way. That is, there is no way for one Document in a given Job to be stapled and another drilled. Also, there is no way for the first sheet of each Document to be on a different media or to have a different value of “sides” from the other Sheets in the Document. In addition, there is no way for one document copy to be printed on paper and another on transparencies. An IPP/1.1 client can specify features, such as finishing, media and sides only at the job level.

The Override Extension defined in this document allows some pages to be affected by attribute values that are Overrides to those specified for the Job as a whole. For example, the first page of a Document has a different media from the rest.

3.1 Numbering of Components

The Override Extension defines a system for numbering of components.

- Each Document has a number. The single Document that a client sends with Print-Job or Print-URI and the first Document that a client sends with Send-Document or Send-URI has the number 1. Each subsequent Document that a client sends has a number that is one higher than the previous.
- Each Page in a Document is numbered sequentially, starting at 1 for the first Page. If a Job has several Documents, the first Page of each Document has the number 1. The Page number is unaffected by the “multiple-document-handling” Job Template Attribute.²
- The Documents are numbered as if the value of “copies” were 1, i.e. if a Document produces multiple copies, each copy has the same document number.
- Each copy of a Document has a number. The first copy of each Document has the number ‘1’, and each subsequent copy has a number that is one higher than the previous copy.

4 New Job Template Attributes

The Override Extension adds a new Job Template attribute: “overrides”. The “overrides” attribute supercedes the “page-overrides” attribute from PWG51000.4

Job Template Attribute	Printer: Default Value Attribute	Printer: Supported Values Attribute
overrides (1setOf collection)	none	overrides- supported (1setOf type2 keyword)

² The primary reason for ignoring “multi-document-handling” in numbering Pages for Overrides is simplicity. From a usability standpoint it is cleaner to present the Page number within a Document than to determine the current rule for numbering Pages across the Job and then keep the counts of the previous Document’s Pages so the correct Page can be specified.

4.1 overrides (1setOf collection)

This OPTIONAL Job Template attribute contains attributes that are associated with Pages and that are treated as page Overrides. Such attributes are called “overrides” attributes. The remainder of this section describes features that an implementation MUST support or MAY support if an implementation supports this attribute.

If this attribute is present in a Job, there are Page Overrides. If it is present, the value consists of one or more ‘collection’ values, where each ‘collection’ value identifies one or more Pages and contains one or more Job Template attributes which act as Overrides to the corresponding Template attribute(s) for the specified Page(s) in the Job. Page Overrides are specified by including the “overrides” attribute in the Job Template attributes group in a Print-Job, Print-Uri, Validate-Job, Create-Job or Set-Job-Attributes operation.

The first member attribute of the “overrides” collection MUST be the “pages” attribute. This identifies the pages to which the Override applies. The identified pages need not be contiguous.

If the Override applies only to specific Documents, the next member attribute MUST be the “document-numbers” attribute. This lists the Documents to which the Override applies. If this attribute is not provided, the Override applies to all Documents in the Job.

If the Override applies only to specific copies of the Document, the next member attribute MUST be the “document-copies” attribute. This details the copies of the Document to which the Override applies. If this attribute is not provided, the Override applies to all copies of the Document.

The remaining member attributes in the ‘collection’ value are the Template attributes that are Overrides for the specified pages.

If the “document-number”, “document-copies” and “pages” identify pages that either don’t exist or are within nonexistent Document-Copies or Documents, the Printer silently ignores them and associates the Overrides with the pages that do exist. See section 4.1.5 for additional information on error handling.

When a client receives this attribute in a Get-Jobs or Get-Job-Attributes response, the value MUST contain the same ‘collection’ values received in Job-Submission operations, except for those ‘collection’ values the Printer returned in the Unsupported Attributes group.

To allow the specification of the last page, copy or document, the MAX integer value (2147483647) is used. To allow the specification of the page, copy or document before the last, a special value of MAX-1(2147483646) is used. No other special values are defined.

Table 1 "overrides" member attributes

<u>Attribute name</u>	<u>syntax</u>	<u>In request</u>	<u>Printer Support</u>
pages	1setOf rangeOfInteger(MAX)	MUST	MUST
document-numbers	1setOf rangeOfInteger(MAX)	MAY	MUST
document-copies	1setOf rangeOfInteger(MAX)	MAY	MAY
Any template attribute		MAY	See section 4.1.4

The following sections describe each member attribute in the above table.

4.1.1 Pages (1setOf rangeOfInteger(1:MAX))

This attribute identifies one or more pages by specifying one or more ranges of numbers (see section 3.1 for the rules on associating a number with each page). The "1setOf" allows noncontiguous pages. The Overrides apply to the identified pages within the Documents specified.

If the "page-ranges" attribute is associated with a Document, the pages identified by this attribute are the same as when "page-ranges" is not present. However, this attribute may identify pages that are deselected for printing by the "page-ranges" attribute. For example, if the value of "page-ranges" is "5:10" and this attribute identifies pages "3:6", this attribute identifies two pages (3 and 4) that are not printed and two that are (5 and 6)

If a Printer support the "overrides" attribute, it MUST support this attribute. A client MUST supply this attribute in each 'collection' value of the "overrides" attribute and it MUST be the second attribute of each 'collection' value.

Note: To allow the specification of the last page the MAX integer value (2147483647) is used. To allow the specification of the next to last page a special value of MAX-1(2147483646) is used. No other special values are defined.

4.1.2 document-numbers (1setOf rangeOfInteger (1:MAX))

This attribute identifies one or more Documents by specifying one or more ranges of numbers. The Overrides apply to the pages within the Documents specified.

A Printer MUST support this attribute. A client MAY supply this attribute in each 'collection' value. If supplied, it MUST be the second attribute of each 'collection' value.

Note: To allow the specification of the last document, the MAX integer value (2147483647) is used. To allow the specification of the next to last document, a special value of MAX-1(2147483646) is used. No other special values are defined.

4.1.3 document-copies (1setOf rangeOfInteger (1:MAX))

This attribute identifies one or more Document-Copies by specifying one or more ranges of numbers. The Overrides apply to the pages within the identified Documents-Copies within the Documents specified. For example, 10 copies are duplex printed on letter paper with a staple, while one copy is simplex printed on transparencies without a staple.

If an attribute can affect a Document, it can affect particular Document-Copies. If an attribute can affect Sheets, it can affect Sheets of particular Document-Copies.

A Printer MAY support this attribute. A client MAY supply this attribute in each 'collection' value. It MUST be the third attribute of each 'collection' value if the client supplied "document-numbers"; otherwise it MUST be second.

Note: To allow the specification of the last document copy, the MAX integer value (2147483647) is used. To allow the specification of the next to last document copy, a special value of MAX-1(2147483646) is used. No other special values are defined.

4.1.4 Overriding template attributes

These attributes have the same meaning as in IPP/1.1. Any template attribute supported by the printer may be supplied. Only those supported attributes that affect Pages, Impressions or Sheets will be honored. For example, if an Override specifies to override the “job-priority” attribute, the Printer will ignore this specification. In order for any overrides to take place, the client MUST include at least one attribute to be overridden, and the Printer MUST support the inclusion of such attributes.

The Printer MAY support any Template attribute with Overrides. The list of Template attributes that the Printer will Override is listed in the Printer’s “overrides-supported attribute. See section 4.1.7.

All overriding template attributes follow the same rules as any Template attributes and interact with “ipp-attribute-fidelity” as specified in [rfc2911]. Therefore if “ipp-attribute-fidelity” is ‘false’, the request MUST accept the request (assuming no other problems are found with the request) and any overriding Job Template attributes not supported by the Printer SHOULD be returned in “unsupported-attributes”. If “ipp-attribute-fidelity” is ‘true’, then the Printer MUST reject the request and the Job Template attributes that affect Jobs MUST be returned in “unsupported-attributes”.

DMC ISSUE01: I'm not sure what the SHOULDs/MUSTs/reject/accept/unsupported should be, so I haven't gotten that all worked out in this paragraph.

4.1.4.1 Template Attributes that affect only whole Jobs

Template Attributes that operate on Jobs, such as “job-priority”, “job-hold-until”, and “multiple-document-handling”, are meaningless as page overrides. These attributes SHOULD NOT be included in “overrides”.

4.1.4.2 Template Attributes that affect only whole Documents

Template Attributes that operate on Documents, such as “copies”, are meaningless as page overrides. These attributes SHOULD NOT be included in “overrides”.

4.1.4.3 Template Attributes that affect only whole Pages

Template Attributes that operate on Pages, such as “page-ranges”, are appropriate as page overrides. These attributes MAY be included in “overrides”.

Template Attributes that operate on Pages do not affect the location of the page image on the sheet.

4.1.4.4 Template Attributes that affect only whole Impressions

Template Attributes that operate on Impressions, such as “image-shift”, are appropriate as page overrides. These attributes MAY be included in “overrides”.

When an Impression attribute changes value, either from one override to another, or from the default to an override, or from an override to the default, this forces the Printer to move on to the next Impression—that is, the next sheet side.

4.1.4.5 Template Attributes that affect only whole Sheets

Template Attributes that operate on Sheets, such as “media” and “finishings”, are appropriate as page overrides. These attributes MAY be included in “overrides”.

When a Sheet attribute changes value, either from one override to another, or from the default to an override, or from an override to the default, this forces the Printer to move on to the first side of a new sheet.

4.1.4.6 Template Attributes Scope for Override

Below is a table that shows the scope to which the Template attribute applies. The Scope is applicable only when the Template attribute is applied as part of an override. As indicated above Template attributes that apply to Jobs or Documents SHOULD NOT be part of an Override. They are meaningless in a Override which act on Pages in a Document. The remaining Template attributes apply to Sheets, Impressions or Pages. The sections above indicate the appropriate behavior for when the attribute values change on Override boundaries.

Table 2 Job Template Attribute Override Scope

Job Template attribute	Override Scope Min	Override Scope Max	Attribute Syntax	Reference
copies	Document	Document	integer(1:MAX)	[rfc2911] §4.2.5
cover-back	Sheet	Sheet	collection	[pwg5100.3] §3.1
cover-front	Sheet	Sheet	collection	[pwg5100.3] §3.1
feed-orientation	Sheet	Document	type3 keyword	[ippsave] §5.1
finishings	Sheet	Sheet	1setOf type2 enum	[rfc2911] §4.2.6 [pwg5100.1] §2
finishings-col	Sheet	Sheet	collection	[pwg5100.3] §3.2
font-name-requested	Page	Document	name(MAX)	[ippsave] §5.2
font-size-requested	Page	Document	integer (1:MAX)	[ippsave] §5.3
force-front-side	Sheet	Sheet	1setOf integer(1:MAX)	[pwg5100.3] §3.3
imposition-template	Impression	Impression	type2 keyword name(MAX)	[pwg5100.3] §3.4
insert-sheet	Document	Job	1setOf collection	[pwg5100.3] §3.5
job-account-id **	Job	Job	name(MAX)	[pwg5100.3] §3.6
job-accounting-sheets	Job	Job	collection	[pwg5100.3] §3.8
job-accounting-user-id**	Job	Job	name(MAX)	[pwg5100.3] §3.7
job-copies	Job	Job	integer(1:MAX)	[jobx] §5.1.
job-cover-back	Job	Job	collection	[jobx] §5.1.
job-cover-front	Job	Job	collection	[jobx] §5.1.
job-error-sheet	Job	Job	collection	[pwg5100.3] §3.9
job-finishings	Job	Job	1setOf type2 enum	[jobx] §5.1.
job-finishings-col	Job	Job	collection	[jobx] §5.1.
job-hold-until	Job	Job	type3 keyword name(MAX)	[rfc2911] §4.2.2
job-hold-until-time	Job	Job	dateTime	[ippsave] §5.4
job-message-to-operator	Job	Job	text(MAX)	[pwg5100.3] §3.10
job-phone-number	Job	Job	text(127)	[ippsave] §5.5
job-priority	Job	Job	integer(1:100)	[rfc2911] §4.2.1
job-recipient-name **	Job	Job	name(MAX)	[ippsave] §5.6
job-save-disposition	Job	Job	collection	[ippsave] §5.7
job-sheet-message	Job	Job	text(MAX)	[pwg5100.3] §3.12

Job Template attribute	Override Scope Min	Override Scope Max	Attribute Syntax	Reference
job-sheets	Job	Job	type3 keyword name(MAX)	[rfc2911] §4.2.3
job-sheets-col	Job	Job	collection	[pwg5100.3] §3.11
media	Sheet	Sheet	type3 keyword name(MAX)	[rfc2911] §4.2.11
media-col	Sheet	Sheet	collection	[pwg5100.3] §3.13
media-input-tray-check	Job	Job	type3 keyword name(MAX)	[pwg5100.3] §3.14
media-type³	Sheet	Sheet	type3 keyword name(MAX)	[upnp], [pwg5100.3] §3.13.2
multiple-document-handling	Job	Job	type2 keyword	[rfc2911] §4.2.4
number-up	Impression	Impression	integer(1:MAX)	[rfc2911] §4.2.9
orientation-requested	Page	Page	type2 enum	[rfc2911] §4.2.10
output-bin	Document	Job	type2 keyword name(MAX)	[pwg5100.2] §2.1
page-delivery	Document	Document	type2 keyword	[pwg5100.3] §3.15
page-order-received**	Document	Document	type2 keyword	[pwg5100.3] §3.16
page-ranges	Document	Document	1setOf rangeOfInteger(1:MAX)	[rfc2911] §4.2.7
pages-per-subset	Job	Job	1setOf integer(1:MAX)	[pwg5100.3] §5.3
pdl-init-file	Document	Document	1setOf collection	[ippsave] §5.8
presentation-direction-number-up	Impression	Impression	type2 keyword	[pwg5100.3] §3.17
print-quality	Page	Impression	type2 enum	[rfc2911] §4.2.13
printer-resolution	Page	Impression	resolution	[rfc2911] §4.2.12
proof-print	Job	Job	collection	[ippsave] §5.9
separator-sheets	Document	Job	collection	[pwg5100.3] §3.18
sheet-collate	Job	Job	type2 keyword	[rfc3381] §3.1
sides	Sheet	Sheet	type2 keyword	[rfc2911] §4.2.8
x-image-position	Impression	Impression	type2 keyword	[pwg5100.3] §3.19.2
x-image-shift	Impression	Impression	integer(MIN:MAX)	[pwg5100.3] §3.19.3
x-side1-image-shift	Impression	Impression	integer(MIN:MAX)	[pwg5100.3] §3.19.4
x-side2-image-shift	Impression	Impression	integer(MIN:MAX)	[pwg5100.3] §3.19.5
y-image-position	Impression	Impression	type2 keyword	[pwg5100.3] §3.19.6
y-image-shift	Impression	Impression	integer(MIN:MAX)	[pwg5100.3] §3.19.7
y-side1-image-shift	Impression	Impression	integer(MIN:MAX)	[pwg5100.3] §3.19.8

³ UPnPv1 and UPnPv2 define a separate MediaType Job Template attribute with the same values as the “media-type” member attribute of “media-col”.

Job Template attribute	Override Scope Min	Override Scope Max	Attribute Syntax	Reference
y-side2-image-shift	Impression	Impression	integer(MIN:MAX)	[pwg5100.3] §3.19.9

4.1.5 Handling of Error conditions

If a client puts a member attribute in some position other than its required position (e.g. “pages” MUST be first), a Printer MUST reject the request with status-code ‘client-error-bad-request’.

For each member attribute in the collection (i.e. “pages”, “document-numbers” and “document-copies”) the client MUST NOT specify values that contain overlapping ranges . Furthermore the ranges MUST be in ascending order. If there are multiple “overrides” in the collection the client MUST NOT specify “overrides” with overlapping documents (i.e. “document-numbers”). The “overrides” in the set must be in ascending order based on the “document-number” collection value. If a request is received by the Printer that does not meet these requirements, the Printer MUST reject the request with status-code ‘client-error-bad-request’

If the “document-number”, “document-copies” and “pages” identify pages that either don’t exist or are within nonexistent Document-Copies or Documents, the Printer silently ignores them and associates the Overrides with the pages that do exist.

4.1.6 Rationale for not having a “overrides-default” attribute

There is no “overrides-default” attribute because it adds complicated rules for a Printer to implement. The problems are best illustrated with examples.

If there were a “overrides-default” and it contained a “sides” and “media” Override for the first page, and if a client submitted a Job with no “sides” attribute and with “media” as a Job Template attribute with no Overrides, a possible meaning is that the Printer uses the client’s requested media for the entire Job and the sides specified by the “sides-default” and the “sides” value in “overrides-default”. So in this example, the Printer ignores the “overrides-default” attribute for “media”, but uses it for “sides” because the Printer uses it for an attribute “xxx” only when it uses “xxx-default”.

4.1.7 overrides-supported (1setOf type2 keyword)

This attribute specifies the supported values of the “overrides” attribute. A client can use this attribute to determine what Override attributes the Printer supports.

This attribute contains the name of each attribute that the Printer supports in a ‘collection’ value of the “overrides” attribute. This attribute MUST contain the keywords “document-numbers” and “pages” because a Printer MUST support these attributes This attribute MUST contain the keywords “document-copies” if the Printer supports overriding of individual copies of a Document. This attribute MUST also contain the name of each attribute that can be anOverride. For example, this attribute contains the keyword “sides” if and only if the Printer supports “sides” in a ‘collection’ value of the “overrides” attribute.

There are no corresponding “document-numbers-supported”, “document-copies-supported”, and “pages-supported” Printer attributes. However, the supported values for all of the other member attributes are indicated by the corresponding “xxx-supported” Printer attributes which are the same values as for the corresponding “xxx” operation or Job/ Template attribute. For example, if “sides” is supported as a member attribute of the “override” collection, then the “sides-supported” Printer attribute indicates the values that are supported both at the job level and as an Override.

5 Examples

This section currently contains examples Overrides. Brackets are used to delimit the beginning and end of each Collection value.

5.1 First Page of Single Document is Letterhead

In the first example, the Printer produces 1 copy of a single Document. It is printed on letter-paper using Print-Job. The first Page of the Document is letterhead paper.

5.1.1 Request.

There is one implied Document A.

```
Print-Job
  job template attributes group
    media: letter
    overrides: {
      pages: 1:1
      media: letterhead }
  end-of-attributes
Document A
```

5.2 First Page of Several Documents is Blue

In the second example, the Printer produces 3 copies of each Document. Each is stapled and printed on letter-paper, two-sided using Create-Job. The first Page of each Document is blue-letter paper and one-sided.

5.2.1 Request.

There are two Documents A and B.

```
Create-Job
  operations attributes group
    document-format: application/PostScript
  job template attributes group
* multiple-document-handling: separate-documents-collated-copies
  sides: two-sided-long-edge
  media: letter
```

```
copies: 3
finishings: stapling
overrides: {
  pages: 1:1
  document-numbers: 1: 2147483647
  sides: one-sided
  media: blue-letter }
end-of-attributes
Send-Document
end-of-attributes
Document A
Send-Document
end-of-attributes
Document B
```

6 Conformance Requirements

This section specifies the Conformance Requirements.

This specification describes overriding attributes on particular pages. If a client or Printer supports this specification, it MUST support these mechanisms.

The following are the conformance rules for Overrides. See section 4.1 for further details on Overrides

1. If a Printer or client supports Overrides, it MUST support
 - 1.1. the “overrides” attribute, and
 - 1.2. the “overrides-supported” attribute, and
 - 1.3. the following member attributes of “overrides”:
 - 1.3.1. “pages”, and
 - 1.3.2. “document-numbers”, and
 - 1.3.3. at least one Job Template attribute that can be overridden (e.g. “sides” or “media”) as defined in another specification.
 - 1.4. The mechanism for Overrides MUST be supported by all Job-Submission operations and Validate-Job.

A conforming Printer MUST handle unsupported attributes correctly. If a Printer receives a “overrides” attribute that contains one or more unsupported members, it MUST return in the Unsupported Attributes group of the response the “overrides” attribute with the unsupported member attributes. The “ipp-attribute-fidelity” attribute determines whether the Printer

- a) rejects the Job or
- b) accepts the Job and ignores the unsupported member attributes.

A client or a Printer OPTIONALLY supports the “document-copies” attribute as a member attribute of “overrides”. If a Printer does not support the “document-copies” member attribute and receives it in “overrides”, it treats the “document-copies” attributes as described in the previous paragraph. If the Printer accepts the Job, it behaves as if the Overrides applied to all copies of the specified documents or pages, i.e. the way the Printer would behave if it supported “document-copies” and the client didn’t supply it.

7 IANA Considerations

This section contains the exact information for IANA to add to the IPP Registries according to the procedures defined in RFC 2911 [RFC2911] section 6.

7.1 Attribute Registration

The attributes defined in this document will be published by IANA according to the procedures in RFC 2911 [RFC2911] section 6.2 with the following path:

`ftp.isi.edu/iana/assignments/ipp/attributes/`

The registry entry will contain the following information:

Reference IEEE-ISTO 5100.n:

`ftp://ftp.pwg.org/pub/pwg/standards/pwg5100.n.pdf`

Job Template attributes:

	Section:
overrides	4.1
pages	4.1.1
document-numbers	4.1.2
document-copies	4.1.3

7.2 Keyword Attribute Value Registrations

The keyword attribute values defined in this document will be published by IANA according to the procedures in RFC 2911 [RFC2911] section 6.1 with the following path:

`ftp.isi.edu/iana/assignments/ipp/attribute-values/`

The registry entry will contain the following information:

Reference IEEE-ISTO 5100.4:

`ftp://ftp.pwg.org/pub/pwg/standards/pwg5100.4.pdf`

8 Internationalization Considerations

The IPP extensions defined in this document require the same internationalization considerations as any of the Job Template attributes defined in IPP/1.1 [RFC2911].

9 Security Considerations

The IPP extensions defined in this document require the same security considerations as any of the Job Template attributes defined in IPP/1.1 [RFC2911].

10 References

[RFC2026]

Bradner, S., "The Internet Standards Process -- Revision 3", RFC 2026, October 1996.

[RFC2565]

Herriot, R., Butler, S., Moore, P. and R. Turner, "Internet Printing Protocol/1.0: Encoding and Transport", RFC 2565, April 1999.

[RFC2566]

deBry, R., Hastings, T., Herriot, R., Isaacson, S. and P. Powell, "Internet Printing Protocol/1.0: Model and Semantics", RFC 2566, April 1999.

[RFC2910]

Herriot, R., Butler, S., Moore, P., Turner, R. and J. Wenn, "Internet Printing Protocol/1.1: Encoding and Transport", RFC 2910, September 2000.

[RFC2911]

Hastings, T., Herriot, R., deBry, R., Isaacson, S. and P. Powell, "Internet Printing Protocol/1.1: Model and Semantics", RFC 2911, September 2000.

[rfc3380] "Internet Printing Protocol (IPP): Job and Printer Set Operations", September 2002, T. Hastings, R. Herriot, C. Kugler, and H. Lewis, <ftp://ftp.rfc-editor.org/in-notes/rfc3380.txt>

[PWG5100.4]

Herriot, R., Ocke, K., "Internet Printing Protocol (IPP): Override Attributes for Documents and Pages", IEEE-ISTO 5100.4-2001, February 7, 2001, <ftp://ftp.pwg.org/pub/pwg/standards/pwg5100.4.pdf>.

[DocObj]

Hastings, T., Zehler, P., "The Printer Working Group (PWG) Standard for The Internet Printing Protocol (IPP): Document Object", IEEE-ISTO PWG Working Draft, May 9, 2003, ftp://www.pwg.org/pub/pwg/ipp/new_DOC/wd-ippdoc10-20030509.pdf.

11 Author's Addresses

Peter Zehler
Xerox Corporation
MS: 0128-30E
800 Phillips Road
Webster, NY 14580-9701

Phone: 585 265-8755

© 2001, 2003, IEEE Industry Standards and Technology Organization. All rights reserved.
The IEEE-ISTO is affiliated with the IEEE and the IEEE Standards Association.
IEEE-ISTO 5100.n is a trademark of the IEEE-ISTO.

Fax: 585 422-7961
e-mail: PZehler@crt.xerox.com

Robert Herriot
Xerox Corp.
3400 Hill View Ave, Building 1
Palo Alto, CA 94304

Phone: 650-813-7696
Fax: 650-813-6860
e-mail: robert.herriot@pahv.xerox.com

Kirk Ocke
Xerox Corporation
800 Phillips Road
Webster, NY 14580

Phone: 716-422-4832
e-mail: Kirk.Ocke@usa.xerox.com

IPP Web Page: <http://www.pwg.org/ipp/>
IPP Mailing List: ipp@pwg.org

To subscribe to the ipp mailing list, send the following email:

- 1) send it to majordomo@pwg.org
- 2) leave the subject line blank
- 3) put the following two lines in the message body:
subscribe ipp
end

Implementers of this specification document are encouraged to join IPP Mailing List in order to participate in any discussions of clarification issues and review of registration proposals for additional attributes and values.

Other Participants:

Ron Bergman - Hitachi Koki Imaging Systems
Dennis Carney - IBM
Lee Farrell - Canon Information Systems
Roelof Hamberg - Océ
Bob Herriot - Xerox
Carl Kugler - IBM
Carl-Uno Manros - Xerox
Ira McDonald - High North Inc.
Hugo Parra, Novell
Gail Songer - Netreon
Jerry Thrasher - Lexmark
Atsushi Uchino - Epson
William Wagner - NetSilicon/DPI
Don Wright - Lexmark
Peter Zehler - Xerox

Dan Calle - Digital Paper
Weihai Chen - Microsoft
Satoshi Fujitani - Ricoh
Tom Hastings - Xerox
David Kellerman - Northlake Software
Harry Lewis - IBM
Satoshi Matsushita - Brother
Paul Moore - Netreon
Stuart Rowley - Kyocera
Geoff Sorod - Software 2000
Shinichi Tsuruyama - Epson
Shigeru Ueda - Canon
Mark Vander Wiele - IBM
Michael Wu - Heidelberg Digital

12 Change Log (informative)

The following summaries of the changes in reverse chronological order:

Version June 2 2003:

1. Incorporated changes from 5/29 review. Refined definitions of Page, Impression and Sheet, added Template scope table, added appendix 1
2. Incorporated changes and editorial fixes from Dennis Carney.

Version May 9 2003:

3. Removed Document Overrides.
4. Moved warning counts and errors to another document(JobX)
5. Renamed Page Overrides to facilitate deprecation of PWG 5100.4

13 Appendix 1 Changes from IEEE ISTO 5100.4-2001

This document supercedes the obsolete IEEE ISTO 5100.4-2001. The main features of 5100.4-2001 include Document-Overrides, Page-Overrides, Subset-Finishing, and Job-Warnings. The changes that this specification has made affect all these features. Below is a summary of the changes.

1. Document-Overrides has been removed. The ability to Override Job Template attributes on a per Document basis is now provided by an explicit Document Object. This is specified in a document that is outside the scope of this specification. The attribute "document-override" and its member attributes are now obsolete.
2. Page-Overrides has been simplified and is described in this specification. Differences include
 - There is no longer any concept of input and output pages, or documents, and the mapping between them.
 - All pages are relative to the Document in which they are contained. Pages within specific copies of a Document is allowed.
 - Special values are defined to specify the last and next to last Page in a Document. The special values also apply to Documents and copies of a Document.
3. Subset-Finishing has been removed. It is now part of a specification on IPP Job Extensions. This specification is outside the scope of this specification.
4. Job-Warnings has been removed. It is now part of a specification on IPP Job Extensions. The new definition supports the count and "job-state-reasons" for warnings and errors. This specification is outside the scope of this specification